

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 December 2003 (18.12.2003)


PCT

(10) International Publication Number
WO 03/104636 A1

- | | | |
|--|------------------------------|--|
| (51) International Patent Classification ⁷ :
31/08, F02G 5/02, F02B 47/02 | F02M 25/022, | Erik [SE/SE]; Dunderbacksvägen 14, S-612 46 Finspång (SE). WESTERMARK, Per [SE/SE]; Hörnäkersvägen 45, S-183 65 Täby (SE). |
| (21) International Application Number: | PCT/SE03/00907 | (74) Agents: SUNDSTRÖM, Per et al.; Stenhanagen Patentbyrå AB, P.O. Box 4630, S-116 91 Stockholm (SE). |
| (22) International Filing Date: | 4 June 2003 (04.06.2003) | (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, JP, KE, KG, KP, KR, KZ, LK, LS, LR, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW. |
| (25) Filing Language: | English | (81) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), European patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, |
| (26) Publication Language: | English | |
| (30) Priority Data:
0201771-3 | 11 June 2002 (11.06.2002) SE | |
| (71) Applicant (for all designated States except US): H E HANSSON AB [SE/SE]; P.O. Box 2037, S-612 02 Finspång (SE). | | |
| (72) Inventors; and
(75) Inventors/Applicants (for US only): HANSSON, Hans- | | |

[Continued on next page]

(54) Title: A METHOD AND A DEVICE FOR PRODUCTION OF MECHANICAL WORK AND COOLING/HEATING IN CONJUNCTION WITH A COMBUSTION MACHINE



(57) Abstract: A device and a method to extract mechanical energy in combination with heat and/or cooling from a combustion engine (2), to which fuel and air is fed, whereby water is added to the combustion engine's inlet air prior to combustion. The combustion engine's flue gas is fed at above-atmospheric pressure to the first stage of a flue gas condenser, from which heat is extracted and utilized by a heat consumer and/or a sorption cycle. After condensation, the water-lean flue gas is reheated in order to avoid ice formation during the final expansion.

WO 03/104636 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS,

JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A method and a device for production of mechanical work and cooling/heating in conjunction with a combustion machine

- 5 The present invention refers to a method and device of the kind defined in the preambles of the appended independent claims.

10 The addition of water vapor to the intake air of a combustion engine is previously known, e.g. from PCT SE 9500026, which reveals a technique in which a combustion engine drives a power generator, heat is extracted from pressurized flue gases, and finally the flue gases are expanded to such a degree that the outlet flue gases obtain low temperatures (below 0 °C) and can be directly utilized for cooling purposes.

- 15 In this above-mentioned type of process, there are certain problems regarding the processes' limited flexibility and incomplete exploitation of available energy.

For example, the electric efficiency and the power output of the process are reduced and ice crystals are formed at the expander exit. These serious drawbacks make operation more difficult and add costs.

- 20 One aim with the invention is therefore to propose a process that offers efficient heat-extraction from the combustion engine's flue gases combined with efficient humidification of the combustion engine's combustion air, at the same time as maximizing the electrical output and efficiency of the process and ensuring the
25 process is water self-sufficient.

These goals are entirely or partly achieved by the method and device defined in the appended independent claims to the method and the device. Embodiments of the invention are defined in the appended dependent claims.

- 30 In a practical and especially favourable form of the invention, a large amount of water is added to the inlet air of the combustion engine. Fuel, air and water vapor are combined so that combustion in the combustion engine occurs close to, if not in, stoichiometric conditions.

- 35 Hereby, a maximum degree of the heat content of the flue gas will be in the form of latent heat that can be effectively utilized at useful temperatures by condensation.

- 40 In order to obtain useful heat, it is especially essential that combustion is performed at near-stoichiometric conditions when condensation is carried out at low over-

pressures Condensation at increased pressure improves temperature performance and improves the feasibility of water self-sufficiency.

5 The extracted heat can be led to a heating net (steam net, hot water net, central heating, district heating, hot tap water etc) and to a sorption cycle in any chosen portion.

10 Furthermore, in tractionary applications with combustion engines or fuel cells, water self-sufficiency and an improved heating yield gives advantages for the generation of comfort heating or the production of sorptive cooling.

The water vapour content of the flue gas will be condensed out at successively declining temperature levels due to a decreasing dew-point temperature during the condensation process.

15 A condenser partitioned into two or more condensing sections is preferred, whereby the heat extracted from the last part of the condenser, which is at the lowest temperature, can be utilised to humidify the inlet air by, for example, transferring heat to the inlet air while simultaneously adding of water.

20 The then humidified inlet air can be compressed, optionally together with the fuel, e.g., natural gas, before it is feed to the combustion engine. This compression can be driven with a turbine (expander) through which the flue gases pass before exiting the process.

25 Prior to this expansion, the exiting flue gases can be heated by, for example, flue gases or hot air from the air charger, via a heat exchanger. The turbine will then generate more shaft work and possibly enough shaft work to compress the fuel/air mixture to the engine. Through obtaining a suitable expander inlet temperature, the formation of ice at the expander outlet is avoided.

30 A sorption cooler, or some other sorption cycle, can be heated by the first condenser section, which extracts heat in the temperature interval of, e.g., 110 °C to 85 °C. In order to reach these comparatively high temperature levels it is necessary to perform the condensation in pressurized condensers placed upstream of the expander. For 35 good temperature performance, near stoichiometric combustion is preferred, which can be obtained by ensuring a high humidity in the combustion air. Since stoichiometric combustion minimizes the dilution of water vapour with inert gases, a

maximal dew point temperature and improved condensation temperature can be obtained.

5 A second condenser section is placed downstream of the first condenser and extracts heat at a lower temperature level to be utilized for humidification of the inlet air to the engine. The second condenser section can work, for example, between 85 °C and 25 °C, and thereby the inlet air can be heated and humidified, for example, from 15 °C to ca 40 – 50 °C before it is compressed in the turbo compressor.

10 Examples of sorption cycles include absorption chillers, absorption heat pumps and sorption dehumidifiers using liquid or solid sorbents. Other examples are sorptive separation processes for the separation of carbon dioxide from the flue gas using monoethyleamine or other solvents. Excellent absorption conditions for carbon dioxide removal can be reached downstream of the second condenser section since
15 the flue gas has a high partial pressure of carbon dioxide (it is pressurized and has a low humidity ratio) and is accessible at low temperature.

The use of a final condenser in the pressurized flue gas is essential for the extraction of heat for the inlet humidifier as it improves the water balance and facilitates the
20 efficient recovery of heat from the flue gas.

The condensers can be made comparatively small in area and volume due to the good heat transfer from the condensing water vapour. The combustion engine type is arbitrary, but can include a shaft to deliver mechanical work to, e.g., a generator for
25 power generation. It may include preheating of the fuel/air mixture prior to the inlet to the cylinders.

Furthermore, prior to the inlet to the cylinders, the air or the air/fuel mixture can be given an additional humidification in a intercooler where the gas is brought in direct
30 contact with liquid water until the gas is nearly saturated with water vapour. Relative humidifies of 80-100% are considered optimal.

Likewise, pressurized fuel cells involving the compression and humidification of the inlet media (air and gaseous fuel) and expansion of the outgoing media, can use
35 similar principles for heat recovery and water reuse. By the use of pressurized flue gas condensation in combination with humidification of the inlet air, large improvements can be made in heat recovery, condensation temperatures and water self-sufficiency.

A dust filter and/or a liquid scrubber can be used for the removal of corrosive or environmentally damaging compounds from the flue gas, the scrubber preferably being placed downstream of the condensing units. The make-up water for the scrubber may be condensate from the condensers. Ammonia gas from nitrogen oxide removal can be captured and dosing of sodium hydroxide improves the removal of acidic compounds such as sulfur dioxide and sulfuric acid. The corrosion of downstream heat exchangers and expanders is prevented in this way. The bleed-off liquid from the scrubber can be treated in conventional ways with filters for the removal of dust and soot and with chemical methods for concentration or modification of the dissolved compounds.

The invention is described and examples are given with references to the enclosed figures.

- 15 Fig. 1 shows schematically a simple design for the condensation of flue gases under atmospheric pressure and thereafter are led to the atmosphere;
- Fig. 2 shows, according to the invention, a process where the flue gas is condensed under pressurized conditions and then reheated, expanded and led to the atmosphere;
- 20 Fig. 3 shows, according to the invention, a process where the flue gas is condensed under pressurized conditions and then recuperated, expanded and submitted to heat recovery before it is led to the atmosphere;
- 25 Fig. 4 shows recovered heat for humidified inlet air and different flue gas pressures.

30 Figure 1 illustrates an inlet pipe 10 to a combustion engine 12. The pipe 10 has an inlet section 11 that receives ambient air which is then fed to a air humidifier 5 that receives heat q_3 and water from a pipe 42. The bleed-off water from the humidifier 5 is removed via an outlet pipe 47. Fuel, e.g. natural gas, is fed to the machine 12, via an inlet to the pipe 10 upstream of the engine 12 or by a direct intake to the machine.

35

A turbocharger 6 is comprised of a compressor 6a that is coupled to an expander 6b. It is shown to be coupled to an electric motor for extra work input. For large engines the compressor and the expander are turbo machines whereas screw,

twinscrew or piston types dominate for smaller engines or similar power sizes in fuel cells. Furthermore, in some applications a pressure regulating outlet valve is used instead of an expander. In the inlet pipe 10 downstream of the compressor 6a is an additional humidifier 7, which works under pressurized conditions and is supplied with water from the pipes 41, 42 and 43. In the humidifier 7 the pressurized air is brought in direct contact with water, which leads to further humidification to nearly saturated conditions, preferably 80-100% relative humidity. Additional external heat q_6 can be added.

10 The combustion engine 12 is coupled to an power generator 19 or another load. The combustion engine 12 is shown to have a flue gas pipe 17 with an expander 6b and further downstream a heat recovery boiler 1, generating a heat stream q_1 which is led away to be utilized.

15 The mixture of water, fuel and air entering the engine 12 is chosen to offer a mixture for combustion that is preferably nearly stoichiometric.

Downstream of the heat recovery boiler 1 the flue gas mainly contains water in gaseous form. The flue gas is treated in a liquid scrubber 2 with water from the pipes 20 41, 44, 31, 45. The pipe 46 is a bleed-off of scrubber effluents containing captured, suspended, and dissolved compounds. The treated flue gas from the scrubber 2 is led to a first condenser 3 from which a heat flow q_2 is extracted, mainly due to condensation of water vapour from the flue gas.

25 The flue gas condensate from condenser 3 is led away by the outlet pipe 31. The outlet flue gas from the condenser 3 is led further to a downstream second condenser 4 that is designed to condense a substantial part of the remaining water vapour, the condensate being removed by pipe 41. The condensate contributes to the water supply of other wet units as it can be led to the scrubber 2 via the piping 44 30 and 45 or led to the humidifier 5 or the pressurized humidifier 7. The condenser 4 is designed to extract a heat flow q_3 , which evaporates the remaining amount of water vapour for establishing a mainly stoichiometric mixture of fuel/air/vapour in the engine 12. The pressurized humidifier 7 is extracting heat from the hot compressed air from the compressor 6a and by supplementary flue gas heat q_5 .

35 The heat flows q_1 , q_2 can be used to supply heat to a heat driven sorption cycle of known type. Such heat driven sorption cycles can preferably utilize heat from heat recovery boiler 1 and the condenser 3. A part of the heat can also be used for other applications such as comfort heating or industrial processes.

The process according to figure 2 is different from figure 1 mainly by subjecting the flue gas to flue gas condensation under pressurized conditions before it is reheated, expanded and led to the atmosphere. The flue gas pipe 17 has a section 71 that collects the outlet gas from the second condenser 4 and a heat exchanger 9 that reheats the flue gas by heat exchange with the flue gas upstream of the scrubber 2. The section 71 the reheater 9 and passes the expander 6b that forms a mean to establish a pressure in the flue gas pipe 17 upstream of the expander 6b. The pressure in the condensing parts should be at least 1,5 bar over atmospheric pressure and preferably more than 2 bar over atmospheric.

Equipment is included for heating and humidification of inlet air (5) as well as a second condensation stage (4) for supplementary condensation of flue gas. A possible design is that these two functions are integrated in the same stage in a way that condensation of flue gas is performed on one side of a heat exchanger area while heating and humidification of inlet air is performed on the other side of the same heat exchanger, the humidification side being wetted by water injection. Another design alternative is to perform the humidification in a packed tower, preferably counter-current with a descending water flow and upwards air flow. The outlet water stream is heated by heat from the final condenser (4) and optionally from other suitable heating sources e.g. oil cooler or generator cooling before it is recirculated to the top of the humidification tower.

In the design according to figure 2 the heat recovery boiler 1 is placed downstream of the engine 12 while the expander 6b is placed in the exit of the flue gas pipe 17.

The design according to figure 3 is mainly different than figure 2 by reheating and recuperating the condensed flue gas to a higher temperature in order to achieve more mechanical work from the expander. It is favorable if the expander work can be sufficient for compressor work thus eliminating or substantially decreasing the need for an input of external work.

With the use of a plant according to figure 2 or 3, a very large part of the energy content of the added fuel can be utilized to drive sorption machines and /or the generation of heat and for power production. The total efficiency is typically in the range of 105-112% , (defined as output energy from the engine divided by the lower heating value of added fuel). This high figure is mainly due to the extensive use of flue gas condensation, whereby the outlet flue gas (71) has a very low energy

content. By reheating the flue gas in the reheater 9, the risk of ice formation in the expander 6b can be avoided as shown in figure 2.

It is shown in figure 2 that a heat flow q_6 can be added to the humidifier 7 when additional water flows (supplied by pipe 43) are added for humidification of inlet air. The heat flow q_6 can e.g. be a portion of q_1 , q_2 or q_4 . As an alternative, the compressed air upstream of expander 6b, can be used as a heat source for reheating the flue gas upstream of the expander 6b to prevent ice formation.

- 10 In figures 2 and 3 it is indicated that several different heat flows are generated in the combustion engine system and, as previously known, these heat flows are transferred to a cooling system, at different temperatures. The heat streams released by cylinder cooling q_4 , and from the heat recovery boiler q_1 are both at temperatures around 100 °C which makes them useful for district heating or for driving sorption
- 15 cycles. The heat flow from the first part of the flue gas condenser, q_4 , can be useful for similar purposes if the temperature is sufficiently high.

- In figure 4 the reference case, represented by curve "Q-ref", shows the recovered useful heat without condensation (i.e. heat recovery from cylinder cooling and
- 20 conventional heat recovery boiler). The recovered heat is given as a % of the lower heating value of the fuel. Similar curves are given for cases using the innovative combination of pressurised flue gas condensation in two stages and inlet air humidification as shown in figures 2 and 3. The curves are called "1 bar", "3 bar" and "5 bar" according to the absolute pressure of the flue gas condensers and they all
- 25 represent stoichiometric combustion conditions.

- Figure 4 shows that pressurised condensing upstream of the expander is an effective measure to improve heat recovery from the flue gases. Compared with atmospheric condensing (1 bar), the temperature of the heat recovered is raised by ca 30 °C at a
- 30 condensing pressure of 3 bars and by 50°C at a condensing pressure of 5 bars. This improved heat recovery depends on the increased condensation rate of water from the flue gas, represented by the latent heat "Q lat", which also improves the minimum temperature level required to achieve a water self-sufficient operation.

- 35 Generator 19 also produces a heat flow q_5 which can be utilised. The heat, q_5 is obtained at a relatively low temperature level and can therefore be beneficially utilized to humidify the process inlet air, through warming the inlet air or humidification water by q_5 , for example, in humidifier 5 or upstream of it. Other low temperature heat sources from, for example, the oil coolant, may also be utilized to

humidify the inlet air. Radiation and convective heat losses to the surrounding air can similarly utilized by using air from the engine casing as inlet air to the humidification tower.

Claims

1. Method for the production of mechanical energy in combination with the extraction of cooling and/or heat in connection with a combustion engine (12), which is fed with fuel and air, whereby the machine's inlet air is combined with water vapor before combustion, **characterized by** the treatment of the combustion engine's flue gas in at least one pressurized flue gas condenser (3), whereby the heat flow from this component is utilized by a heat consumer and / or a sorption cycle, and that the flue gas after condensing, but before expansion in a turbine (6b), is reheated in order to avoid ice formation during said expansion.
2. The method according to claim 1, **characterized by** the addition of water vapor and / or condensate from the condenser stages (3,4) to the inlet air.
3. The method according to claim 1 and 2, **characterized by** carrying out flue gas condensing at a flue gas pressure that is at least 2.5 bar absolute pressure, preferably over 3 bar absolute pressure.
4. The method according to parts of claim 1-3, **characterized by** subjecting the combustion engine's inlet air to diabatic humidification at close to atmospheric pressure, whereby heat is transferred from the second stage of the flue gas condenser (4), downstream of the first flue gas condenser stage (3).
5. The method according to parts of claim 1-4, **characterized by** subjecting the combustion engine's inlet air to humidification at raised pressure, through the direct contact between water and compressed air.
6. The method according to parts of claim 1-5, **characterized by** carrying out combustion with an essentially stoichiometric mixture of fuel/air/water.
7. The method according to parts of claim 1-6, **characterized by** reheating the flue gas, after flue gas condensing has occurred, by transferring heat from a warmer part of the flue gas or from the compressed inlet air.
8. The method according to parts of claim 1-7, **characterized by** further heating the reheated flue gas (73) with uncooled flue gas from the combustion engine, whereby the temperature difference between the streams 17 and 73 is under 200 °C and preferably under 100 °C.

9. The method according to parts of claim 1-8, **characterized by** the use of heat flows from the generator (19), oil coolant, or other waste heat flows from the motor to humidify the inlet air to the combustion engine.

5 10. A device to produce mechanical energy and heat and /or cooling in connection with a combustion engine which has the means to humidify the machine's inlet air, **characterized by** a device to recover heat at elevated pressures from the machine's (12) flue gases, by means of flue gas condensing, which is transferred to a heating net or to a sorption cycle in chosen proportions, and a device to reheat the
10 cooled flue gas after flue gas condensing such that the final expansion can be carried out without ice formation.

11. A device according to claim 10, **characterized by** the addition of water vapor and / or condensate to the inlet air by means of using condensate from the
15 condenser stages (3,4).

12. A device according to parts of claims 10-11 **characterized by** the means (6b) to maintain the flue gases at above-atmospheric pressures in the exit pipe from the combustion engine (12) until a position downstream of the condensers (3,4).
20

13. A device according to parts of claims 10-12 **characterized by** the means (6b) to add fuel, air and water vapor to the combustion engine to obtain essentially stoichiometric combustion.

25 14. A device according to parts of claims 10-13 **characterized by** the means to transfer the heat for humidifying the intake air, preferably at the humidification means (5), from the power generator, oil cooling or radiation and convection losses.

15. A device according to parts of claims 10-14 **characterized by** when the
30 combustor engine consists of a pressurized fuel cell.

16. A device according to parts of claims 10-15, **characterized by** the use of extracted heat to drive sorption processes for carbon dioxide removal, where the adsorption unit is preferably placed downstream of the final condenser.
35




Fig 2.




Fig 3.




Fig 4.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00907

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F02M 25/022, F02M 31/08, F02G 5/02, F02B 47/02
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F02M, F02G, F02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 19538067 A1 (ERDGAS ENERGIE SYSTEME GMBH), 17 April 1997 (17.04.97), column 2, line 43 - line 68, figure 1 --	1-16
X	US 4611557 A (HIERZENBERGER), 16 Sept 1986 (16.09.86), figures 1,1A, abstract --	1-16
X	EP 0305351 A2 (TIBERG, LARS), 1 March 1989 (01.03.89), figures 1,2, abstract --	1-16
X	DE 3142851 A1 (SCHUMANN, GERHARD), 1 June 1983 (01.06.83), figure 1, abstract --	1-16

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"Z" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

2 Sept 2003

03 -09- 2003

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Dan Ionesco / JA A
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 90/0907

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 9807975 A1 (ABB POWERMAN AB), 26 February 1998 (26.02.98), page 1, line 26 - page 2, line 9, figures 1,2, abstract --	1-16
X	DE 3333069 A1 (WIESER, RUDOLF), 21 March 1985 (21.03.85), figures 1-6, abstract -- -----	1-16

INTERNATIONAL SEARCH REPORT
Information on patent family members

26/07/03

International application No.

PCT/SE/000907

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	19538067	A1	17/04/97	DE 59603507 D EP 0854978 A,B WO 9714884 A	00/00/00 29/07/98 24/04/97
US	4611557	A	16/09/86	AT 30459 T CS 269973 B CS 8506906 A DE 3560845 D EP 0177484 A,B SE 0177484 T3 HU 42590 A HU 201982 B JP 61085565 A	15/11/87 14/05/90 13/10/89 00/00/00 09/04/86 28/07/87 28/01/91 01/05/86
EP	0305351	A2	01/03/89	DK 473388 A FI 883883 A SE 458800 B SE 8703338 A US 4918916 A US 4945829 A	01/03/89 01/03/89 08/05/89 01/03/89 24/04/90 07/08/90
DE	3142851	A1	01/06/83	NONE	
WO	9807975	A1	26/02/98	SE 9603033 D	00/00/00
DE	3333069	A1	21/03/85	NONE	